



# **COLARIS.12-2200**

# SMALL PRODUCTION INKJET PRINTER FOR TEXTILES, CARPETS, MATS AND PIECE GOODS



#### STANDARD FEATURES

- Ink tanks with 5 I content
- 3-stage ink filtration system
- Ink and print-head heating and cooling for constant temperature
- Ink circulation system for trouble-free print performance
- Automatic print head cleaning with water and vacuum extraction
- Height adjustment up to 50 mm (for sheets, tiles, pieces)
- Precise servo drives for print head and conveyor
- Control system with USB interface
- Windows based printing software
- Print heads with 7, 12, 30 or 80 pl base droplets
   —for best match of application
- Permanent gluing device to create a "sticky belt"
   (i.e. to print textiles or nonwoven products)

#### **OPTIONS**

- Integrated unrolling for small batch operation
- Positioning device to print carpet tiles, mats and sheet material in perfect registration
- Conveyor belt with pins for carpet products
- Washing device for transport blanket to clean-up any overprints
- Second vacuum system to operate the printer with completely different ink types (penetration booster) at the same time
- 2 print heads per color for double speed
- Different dryers or steamers for dye fixation

## **APPLICATIONS**

- Carpet tile or carpet mat printing
- Printing on ready made terry towels
- Small production printing of roll-to-roll goods
- Printing on sheet material

## **INK FAMILIES**

- Acid for polyamide, silk and wool
- Reactive for cellulose, cotton, linnen
- Disperse for polyester, EDP, CDP and Sorona
- Pigment for any substrate
- VAT for cellulose and cotton

#### **POST PROCESS**

Depending on ink family, fiber type and application - **ZIMMER AUSTRIA** offers a wide range of fixation and post-processing systems and equipment like steamer, washer, hot air dryer, infrared fixation ...



#### **COLARIS.12 - 2200 - Small Production Printer Electric requirements** 3 PH, 400/230 V, 50 or 60 cycles Connected load is about 20 kVA **Electrical load** Average power consumption is about 5 kW Air supply 6-8 bar; oil-free and dust-free 2-3 bar soft water (for blanket washer) Water supply Size / weight 220 x 520 cm (7 \* 17ft) / 3 tons Max. print width 2200 mm No. of colors/jetting fluids 6 or 12 Print heads per color 1 (up to 12 colors) or 2 (up to 6 colors) 170 m<sup>2</sup>/hour at 400\*400 dpi (draft mode) Print capacity with 1 head 85 m<sup>2</sup>/hour at 400\*800 dpi per color 50 m<sup>2</sup>/hour at 800\*800 dpi Print capacity with 2 heads 155 m<sup>2</sup>/hour at 400\*800 dpi 90 m<sup>2</sup>/hour at 800\*800 dpi per color (max. 6 colors) StarFire<sup>TM</sup> with 7, 12, 30 or 80 picolitre native drop size Print head model Print resolution "X" From 200 to 1,600 dpi (in steps of 100 dpi) Print resolution "Y" Native head res. 400 dpi (max. 1,600 dpi at 4 passes) Piece good is about 30% slower in comparison to roll-to-



Zimmer Maschinenbau GmbH
DIGITAL PRINTING SYSTEMS
Eibergstrasse 2-8
6330 Kufstein | AUSTRIA

Phone +43 (5372) 648 93 - 0 info@zimmer-austria.com

**INNOVATION** 

Tile, mat or sheet goods:

QUALITY

roll production. Pieces up to 2x1 m in size can be printed.

**SERVICE** 

J. ZIMMER Maschinenbau GmbH, Kufstein reserves the right of technical and design modification of the equipment described within this brochure at any time without prior notice. This leaflet is for informative purpose only.